



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467



WorldWide
ELECTRIC CORPORATION

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



DATA SHEET

Premium Efficiency Motor: **SSPE2-18-56CRD,**

60 Hz

Document Generated: 22-Feb-2023
Document ID:

Customer:

MOTOR INFORMATION

HP	2
RPM	1800
Phase	3
Frequency	60
Voltage	230/460
Frame Size	56C
Enclosure	TEFC
Degree of Protection	IP69K
Service Factor	1.15
Poles	4
Full Load	1750
Speed	F
Temperature Class	80°C
NEMA Code Letter	L
Duty Cycle	S1
Slip	2.78%
NEMA Design	B
Moment of Inertia	0.184 lb.ft.^2
Locked Rotor Time	12 seconds
(Hot) Sound Pressure	61 dB(A)
Number of Starts	12
Max Ambient Temperature	40° C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bidirectional
Area of Classification	Div.2 Class I, Gr. A,B,C&D T2B
Inverter Rating	10:1 CT/20:1 VT
Standard	NEMA MG1,
Approvals	UL1004 CSA,UL,CE

EFFICIENCY/POWER

FACTOR	LOAD	EFF	P. F.
100%		86.5	
%	0.7883	50%	0.6
50%		6	
		80.0 %	0.5
		2	

TORQUE

FULL LOAD	LRT	BD
5.9 lb.ft.	285 %	300 %

AMPERAGE INFORMATION

	230V	460
Full Load Amps	V	
Locked Rotor	6	3
Amps No Load	50	25
Current Usable at 208V	3.5	6
		1.75

BEARING INFORMATION

DE Bearing	6205 2RS
ODE	6205 2RS
Bearing	Mobil Polyrex
Grease Type	EM

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	304 Stainless Steel
Connection Diagram	9 Lead 2Y/Y
Approximate Weight	50 lbs.



Electrical Helper.org

For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467


**AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL**

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



MOTOR DRAWING

Premium Efficiency Motor: **SSPE2-18-56CRD**



DIMENSION - INCHES

FLANGE MOUNTING						C	P	T	AB
AK	BD	AJ	BF	BB	BC				
4.5	6.45	5.875	4*3/8-16	0.16	-0.19	13.75	6.95	N/A	5.95

SHAFT & KEY					
S	ES	R	N-W	U	AH
0.188	1.41	0.517	1.88	0.625	2.06

TERMINAL BOX				
AA	AB	AC	RD	BV
1/2 NPT	5.95	4.5	3.45	4.75



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



PERFORMANCE CURVES

Premium Efficiency Motor: **SSPE2-18-56CRD**


Document Generated: 31-Jan-2023
Document ID:

Customer:


Motor Type	SSPE		FL Speed	1750	
Output Rating	2		LRT (%FLT)	285	460 volt FLA 3
(HP) Full Load	5.9	lb.ft	BDT (%FLT)	300	230 volt FLA 6
Torque Rotor	0.184	lb-ft^2			

Wk^2

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE





NAMEPLATE / WIRING

Premium Efficiency Motor:

SSPE2-18-56CRD

Document Generated: 31-Jan-2023

Customer:

Document ID:

SAMPLE NAMEPLATE DATA

		THREE PHASE AC INDUCTION MOTOR				NEMA®	
		INVERTER DUTY 20:1 VT 10:1 CT				Premium	
Model .		FRAME		IP 69K	LB/WT		
Hz 60	S. F. 1.15	Hz 50	S. F. 1.15	ENCL. TEFC	AMB. 40°C		
HP	RPM	HP	RPM	DUTY CONT	INS. F		
VOLTS 230/460		VOLTS 190/380		NEMA DES. B			
AMP		AMP		BRG DE			
CODE	P. F.	CODE	P. F.	BRG ODE			
EFF	MIN	IE3 -		NO.			
				C 502259 US		E 517327	
CC082A							

Model	SSPE2-18-56CRD	FRAME	56C	LB/WT	50 lbs.
Hz	60	S.F.	1.15	Hz	50
HP	2	RPM	1750	HP	1 1/2
VOLTS	230/460	VOLTS	190/380		
AMPS	6/3	AMPS	5.2/2.6		
CODE	L	P.F.	0.78	CODE	M
EFF	86.5%	MIN	80%	IE3 -	
	84.1% BRG DE	6205 2RS			
	BRG ODE	6205			
	2RS				