

DATA SHEET

Premium Efficiency Motor: **SSPE3-12-213TCRD,**

60 Hz



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



WORLDWIDE
ELECTRIC CORPORATION



Document Generated: 22-Feb-2023
Document ID:

Customer:

MOTOR INFORMATION

HP	3
RPM	1200
Phase	3
Frequency	60
Voltage	230/460
Frame Size	213TC
Enclosure	TEFC
Degree of Protection	IP69K
Service Factor	1.15
Poles	6
Full Load	1175
Speed	F
Temperature Class	80°C
NEMA Code Letter	K
Duty Cycle	S1
Slip	2.08%
NEMA Design	B
Moment of Inertia	1.055 lb.ft.^2
Locked Rotor Time	12 seconds
(Hot) Sound Pressure	61 dB(A)
Number of Starts	12
Max Ambient Temperature	40° C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bidirectional
Area of Classification	Div.2 Class I, Gr. A,B,C&D T2B
Inverter Rating	10:1 CT/20:1 VT
Standard	NEMA MG1,
Approvals	UL1004 CSA,UL,CE

EFFICIENCY/POWER

FACTOR LOAD	EFF	P. F.
100%	89.5	
%	0.74875%	0.6
50%	2	
	86.0 %	0.5
	1	

TORQUE

FULL LOAD	LRT	BDT
13.2 lb.ft.	250 %	280
%		

AMPERAGE INFORMATION

	230V	460
Full Load Amps	V	
Locked Rotor	9.2	4.6
Amps No Load	64	32
Current Usable at 208V	6	10

BEARING INFORMATION

DE Bearing	6308 2RS
ODE	6208 2RS
Bearing	Mobil Polyrex
Grease Type	EM

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	304 Stainless Steel
Connection Diagram	9 Lead 2Y/Y
Approximate Weight	168.5 lbs.



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467


AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



MOTOR DRAWING

Premium Efficiency Motor: **SSPE3-12-213TCRD**



DIMENSION - INCHES

FLANGE MOUNTING						C	P	T	AB
AK	BD	AJ	BF	BB	BC				
8.5	10.08	7.25	4*1/2-13	0.25	0.25	20.7	10.7	1.75	7.85

SHAFT & KEY					
S	ES	R	N-W	U	AH
0.312	2.41	1.201	3.38	1.375	3.12

TERMINAL BOX				
AA	AB	AC	RD	BV
1/2 NPT	7.85	6.41	3.95	11.15



Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL
Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



PERFORMANCE CURVES

Premium Efficiency Motor:

SSPE3-12-213TCRD

Document Generated: 31-Jan-2023


Document ID:

Customer:


Motor Type	SSPE		FL Speed	1175	
Output Rating	3		LRT (%FLT)	250	460 volt FLA 4.6
(HP) Full Load	13.2	lb.ft	BDT (%FLT)	280	230 volt FLA 9.2
Torque Rotor	1.055	lb-ft^2			

Wk^2

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE





Electrical Helper.org
For All Your Electric Needs Since 1928
411 N Platte Ave. York, NE. 68467

AC-DC MOTORS :: SALES & SERVICE
REWINDING :: CUSTOM CONTROL PANEL

Kelly MacMillan
Office Ph: 888-226-4917
Fax: 888-226-4917
Cell: 402-679-1579
E-Mail: kelly@electricalhelper.com



NAMEPLATE / WIRING

Premium Efficiency Motor:

SSPE3-12-213TCRD

Document Generated: 31-Jan-2023

Customer:

Document ID:

SAMPLE NAMEPLATE DATA

		THREE PHASE AC INDUCTION MOTOR				NEMA® Premium	
		INVERTER DUTY 20:1 VT 10:1 CT					
Model .		FRAME		IP 69K	LB/WT	230V 	
Hz 60	S. F. 1.15	Hz 50	S. F. 1.15	ENCL. TEFC	AMB. 40°C		
HP	RPM	HP	RPM	DUTY CONT	INS. F		
VOLTS 230/460		VOLTS 190/380		NEMA DES. B		460V 	
AMP		AMP		BRG DE			
CODE	P. F.	CODE	P. F.	BRG ODE			
EFF	MIN	IE3 -		NO.			
						CC082A	

Model	SSPE3-12-213TCRD			FRAME	213TC		LB/WT	168.5 lbs.	
Hz	60	S.F.	1.15	Hz	50		S.F.	1.15	
HP	3	RPM	1175	HP	2		RPM	980	
VOLTS 230/460				VOLTS 190/38					
AMPS 9.2/4.6				AMPS 0					
CODE	K	P.F.	0.74	CODE	7.6/3.8		B.B.	0.70	
EFF	89.5%	MIN	86%	IE3 -					
82.5% BRG DE 6308									
2RS BRG									
ODE 6208 2RS									